In re:

**Thomas Boucino** 

Serial No.:

09/591,349 June 9, 2000

Filed:

Page 2 of 7

 $\mathcal{E}'$ 

a twisted pair of insulated conductors disposed in one of the plurality of compartments.

13. (four times amended) A communications cable comprising: a cable jacket;

a spacer extending within said cable jacket, the spacer being formed of and having an outer surface of a polymeric material and having a longitudinally extending center portion and plurality of longitudinally extending wall portions radiating from said center portion such that the cross-section of the spacer is radially symmetric, the longitudinally extending wall portions having a first radial section that increases in thickness with distance from the center portion and a second radial section that decreases in thickness with distance from the center portion, the spacer and the cable jacket defining a plurality of compartments within the cable jacket; and

a twisted pair of insulated conductors disposed in at least one of the compartments.

25. (four times amended) A communications cable comprising: a cable jacket;

a spacer extending within said cable jacket, the spacer being formed of a polymeric material and having a longitudinally extending center portion and plurality of longitudinally extending wall portions radiating from said center portion such that the cross-section of the spacer is radially symmetric, the longitudinally extending wall portions including a first section having a first thickness, a second section having a second thickness and a third section having a third thickness, the third thickness being different from the first and second thickness, the third section located between the first section and the second section, the spacer and the cable jacket defining a plurality of compartments within the cable jacket; and

a twisted pair of insulated conductors disposed in at least one of the compartments.

40. (twice amended) A communications cable comprising: a cable jacket;

E4